(12) UK Patent Application (19) GB (11) 2 184 706 (13) A

(43) Application published 1 Jul 1987

- (21) Application No 8628426
- (22) Date of filing 27 Nov 1986
- (30) Priority data
 - (31) **8531561 8619894**
- (32) 21 Dec 1985 15 Aug 1986
- (33) GB
- (71) Applicant

 James Industries Limited,

(Incorporated in United Kingdom),

St Catherine Street, Gloucester GL1 2SL

- (72) Inventor

 David Richard James
- (74) Agent and/or Address for Service S. Jones-Robinson, c/o Mecanaids Limited, St Catherine Street, Gioucester GL12SL

- (51) INTCL⁴ A61G 7/10
- (52) Domestic classification (Edition I)

 88H KE

 U1S 1061 B8H
- (56) Documents cited GB 1353419
- (58) Field of search

 88H

 A4L

 Selected US specifications from IPC sub-class A61G

(54) Invalid hoists

(57) An invalid hoist has a lifting arm 4, a sling hanger support 12 mounted to turn about a rigid vertical bearing axis V at the outer end of the arm 4 and a sling hanger 10 which is a unitary construction pivotable about a horizontal axis H relative to the support 12. The hanger 10 presents spaced sling attachment points on both sides of the axis H for connection of one pair of sling attachments 41 to one side of the axis H and for connection of a second pair of sling attachments 41 to the opposite side of the axis H. Thus the disposition of a invalid I can be changed whilst suspended on the hoist by pivotal movement of the hanger 10 about the horizontal axis H. The pivotal movement of the hanger can be controlled by frictional restraints which are infinitely variable, or by a spring-loaded catch which allows location in pre-selected positions. Both pairs of attachments 41 may be widely spaced, or one pair closely spaced.




FIG 1